

Multifunction Tool

When processing a number of construction projects, builders need to carry a variety of tools for the construction. This causes builders trouble for carrying them around. This multi-function series is smaller and lighter, easier to change molds, faster operation. It minimizes the inconvenience during the construction.



REC-5250M

Battery-Powered Type

- ◆ The EHV rechargeable host and the DC-driver-motor-hydraulic pump drive high tonnage output. The output pressure: 700kg/cm² (10000psi) – Has two-stage inlet, high and low pressures.
- ◆ Easy to operate, lightweight and easy to carry, high mobility. Suitable to use in fast-rescue construction sites.
- ◆ The hydraulic system is designed with an overload protection device, which is much secured, not easy to damage.
- ◆ The multi-functional combination makes investment low pay high.
- ◆ The head is made of high-strength alloy steel, which can be rotated 180 degrees to coordinate with various angles.

| Item | Output (Ton) | (VDC) | Weight (Kg) | Remark |
|-----------|-----------------|-------|----------------|------------------------------------|
| REC-5250M | 10 | 14.4 | 4.3 | Accessory Battery x2 Charger x1 |

CPO-5250M

Directly Type

- ◆ The Integrated hydraulic crimping EHV machine has two-stage, high and low pressures, oil output by squeezing manually. The maximum output pressure: 700kg/cm² (10000psi).
- Easy to operate, lightweight and easy to carry. Suitable to use on aerial pole works.
- ◆ The hydraulic system is designed with an overload protection device, which is much secured, not easy to damage.
- ◆ The multi-functional combination makes investment low pay high.
- The head is made of high-strength alloy steel, which can be rotated 180 degrees to coordinate with various angles.

| Item | Output (Ton) | Weight (Kg) |
|-----------|-----------------|----------------|
| CPO-5250M | 10 | 3.8 |





CO-5250M

Separate Type

- ◆ A single-loop crimping tool has lightweight, easy to carry and operate.
- ◆ It is mainly made of high-carbon steel, which had hardness heat treatment that has high tension resistance, not easy deformation.
- ◆ The multi-functional combination makes investment low pay high.
- ◆ Need to coordinate with hydraulic pump (power pump: CTE-25AS, hand pump: CP-700, or foot pump: CFP-800).

| Item | Output (Ton) | Weight (Kg) |
|----------|-----------------|----------------|
| CO-5250M | 10 | 2 |