

SPS-700

Japan Pressure Regulating Valve

- ◆ Riken Manufacturing.
- ◆ Adjustable pressure value, with seven-segment regulator.
- ◆ Automatic power when pressure reaches.



SMVT-43

Four Way Three Position Valve

- ◆ Enter, return oil, double return way of action controlled.
- ◆ Can control and operate alone.
- ◆ Applicable to double-acting hydraulic cylinder.

Multi-Way Valve

- ◆ Made in Germany.
- ◆ Max. pressure withstand 700 kg / cm².
- ◆ Single-hole, 3/8 "NPT.
- ◆ Double return way of oil-controlled valve.



V-1

Two way ball valve



V-2

Three way ball valve



V-2-1

Multi-Way Valve

- ◆ You can connect with two or more loops.
- ◆ Can be used with a variety of different tools.
- ◆ Max. pressure withstand 700 kg / cm².



Length

mm	x0.03937	=	inch	x25.4
cm	x0.3937	=	inch	x2.54
m	x3.28	=	foot	x0.305

Force

newton(N)	x0.225	=	inch	x4.45
cm	x225	=	inch	x0.00445

Area

mm ²	x0.00155	=	inch ²	x645
cm ²	x0.155	=	inch ²	x6.45
m ²	x10.8	=	foot ²	x0.0929

Torque

newton mwtter (Nm)	x8.9	=	inch ²	x0.113
newton mwtter (Nm)	x0.74	=	inch ²	x1.36

Volume

cm ³	x0.061	=	inch ³	x16.4
liter(L)	x61	=	inch ³	x0.016
ml(cm ³)	x0.034	=	oz-liq	x29.6
liter(L)	x1.06	=	quart	x0.946
liter(L)	x0.26	=	gallon	x3.79

Pressure(Pa=N/m²)

kPa	x0.145	=	p.s.i	x6.89
kgf/cm ²	x14.23	=	p.s.i	x0.07
Bar	x14.5	=	p.s.i	x0.0689
Bar	x1.02	=	kgf/cm ²	x0.981

Mass

g	x0.035	=	ounce	x28.3
kg	x2.2	=	pound	x0.454
metric ton (t)	x1.1	=	ton(short)	x0.907
metric ton (t)	x9.8	=	kN	x0.102

Power(W=J/s)

kw	x1.34	=	hp	x0.746
watt(w)	x0.74	=	ft.lb/s	x1.36